



T800 Android Fully Rugged Tablet

- 8.1" HD LumiBond® display for better viewing experience
- Getac proprietary SnapBack add-on featuring Smart card and contactless RFID reader Combo or 2nd expanded battery
- Optional 1D/2D imager barcode reader,
 Serial port, MicroSD or Ethernet
- LifeSupport™ battery swappable technology for uninterrupted battery life
- MIL-STD-810G and IP65 certified













Office Dock



SnapBack Add-on



T800 Android Fully Rugged Tablet

Specification

Operating System Android 4.4

Mobile Computing Platform

Intel® Celeron® N2930 1.83 GHz, burst up to 2.16 GHz

- 2MB cache

VGA Controller

Intel® HD Graphics

Display

8.1" TFT LCD HD (1280 x 800) 600 nits LumiBond® display with Getac sunlight readable technology

Storage & Memory

2GB DDR3L SSD 32GB / 64GB

Keyboard

6 tablet buttons (Power, Camera Capture,

Recent APPs/Barcode Reader Trigger, Android Home, Volume Up, Volume Down)

Pointing Device

Touchscreen

- Capacitive multi-touch screen - Optional dual mode touchscreen (multi-touch and digitizer)

Expansion Slots

Optional 1D/2D imager barcode reader, Serial port,

MicroSD or Ethernet Optional SnapBack add-on:

Smart card and contactless RFID reader comboii

Optional SnapBack add-on: 2nd expanded battery

I/O Interface

HD webcam x 1

8M pixels auto focus rear camera x 1

USB 3.0 (9-pin) x 1

Headphone out/Mic-in Combo x 1

DC in Jack x 1 Micro HDMI x 1

Docking connector (24-pin) x 1

Optional RF antenna pass-through for GPS, WWAN and WLAN

Communication Interface

Optional 10/100/1000 base-T Ethernet (occupies expansion slot)

Intel® Dual Band Wireless-AC 7260, 802.11ac

Bluetooth (v4.0 class 1) Optional dedicated GPS

Optional Gobi™ mobile broadband

Software

Getac File Manager **GPS-Ecompass** Barcode Reader Utilityⁱⁱⁱ

Security Features

Optional SnapBack add-on: Smart card and contactless RFID

reader comboi

AC adapter (65W, 100-240VAC, 50 / 60Hz)

Li-Ion battery (7.4V, 4200mAh)

LifeSupport™ battery swappable technology (only with SnapBack 2nd expanded battery)

Dimension

(W x D x H) & Weight

227 x 151 x 24 mm (8.93" x 5.94" x 0.94")

0.88kg (1.94 lbs)vi

Rugged Features

MIL-STD-810G certified and IP65 certified 6 feet drop resistant Optional ANSI/ISA 12.12.01

Vibration & drop resistant e-Mark certified for vehicle usage

Environmental Specifications

Temperaturevii:

- Operating: -21°C to 50°C / -5.8°F to 122°F - Storage: -40°C to 71°C / -40°F to 160°F

Humidity:

- 95% RH, non-condensing

Accessories

Carry bag Battery charger

Multi-Bay Charger (Eight Bay) Main battery (7.4V, 4200mAh) 2nd expanded battery (14.4V, 2100 mAh)

AC adapter (65W, 100-240VAC)

Vehicle adapter (90W, 11-16V DC and 22-32V DC)

Capacitive stylus & tether

Digitizer pen

Shoulder strap (2-point)

Hand strap Wrist strap Protection film Vehicle cradle Vehicle dock Office dock

Docking solution

	Microphone	Audio Output	DC in Jack	USB	LAN	RF antenne connector (WWAN, WLAN, GPS)
Vehicle Dock			1	2	1	3
Office Dock	1	1	1	4	1	

- Barcode reader, Serial, Ethernet, and MicroSD port are mutually exclusive options

www.getac.com

- Barcode reader, Serial, Ethernet, and MicroSD port are mutually exclusive options.

 All SnapBack add-ons are mutually exclusive options.

 Available for barcode reader option.

 13.56MHz Contactless RFID and Smart Card reader (ISO 15693 and 14443 A/B compliant).

 Battery performance will vary upon software applications, wireless settings, power management settings, LCD brightness, customized modules and environmental conditions. The battery performance will vary upon software applications, wireless settings, power management settings, LCD brightness, customized modules and environmental conditions. The battery has a limited number of charge cycles and may eventually need to be replaced by a Getac service provider. Battery life and charge cycles vary by use and settings.
- Weight varies from configurations and optional accessories.
 Tested by a national independent third party test lab following MIL-STD-810G



Getac Technology Corporation

5F, Building A, No. 209, Section 1, Nangang Rd., Nangang Dist., Taipei City, 11568, Taiwan, R.O.C. Tel: +886 2 2785 7888 globalmarketing@getac.com

Copyright © 2015 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved All specifications are subject to change without notice. V03M11Y15WW