Z76



2MP Outdoor Dome with D/N, Adaptive IR, Basic WDR, SLLS, Fixed Lens

- 2 Megapixel
- Day & Night with Superior Low Light Sensitivity and Adaptive IR LED
- Fixed Lens with f2.8mm/F2.0
- Basic WDR
- H.265 Compression
- Super wide angle
- Event trigger, response and notification

Specifications

Device		
Product Type	Dome	
Maximum Resolution	2MP	
Application Environment	Outdoor	
Image Sensor	Progressive Scan CMOS	
Sensor Size	1/2.7 "	
Day / Night	Yes	
Low Light Sensitivity	Superior	
Minimum Illumination	Color: 0.028 lux; B/W: 0 lux (IR LED on)	
Mechanical IR Cut Filter	Yes	
IR LED	Adaptive IR LED (850 nm)	
IR Working Distance	30m	
Electronic Shutter	1/3-1/100000 second (auto mode)	
Lens		
Focal Length	Fixed focal, f2.8mm	
Aperture	F2.0	
Lens Mount	Board mount	

Dome Camera

Horizontal Viewing Angle	114°
Vertical Viewing Angle	62°
Viewing Angle Adjustment	Pan: 0°-360°, Tilt: 0°-75°, Rotation: 0°-360°

Video

H.265, H.264 (Baseline/ Main/ High profile), MJPEG
30 fps at 1920 x 1080 30 fps at 1280 x 960 30 fps at 1280 x 720 30 fps at 640 x 480 30 fps at 640 x 360 30 fps at 320 x 240
Simultaneous dual streams
32Kbps - 8Mbps (per stream)
Basic WDR (80 dB)
White Balance, Saturation, Brightness, Contrast, Sharpness, Automatic gain control
3D DNR
Yes
Yes

Audio

Audio Type	1-way, Built-in Microphone
Audio Compression	G.711, G.722.1, G.726, MP2L2, PCM

Event

vent Trigger


Integration


ONVIF Compliant Yes, Profile S	ONVIF Compliant
--------------------------------	-----------------

General

Power Source	DC 12V, PoE
Power Consumption	5 W (DC), 6.5 W (PoE)
Weight	354g (0.8lb)
Dimensions	(Ø x H): 110mm x 94.4mm (4.3" x 3.7")
Environmental Casing	Weatherproof (IP66)
Starting Temperature	-30°C ~ 60°C (-22°F ~ 140°F)
Operating Temperature	-30°C ~ 60°C (-22°F ~ 140°F)
Warranty	2 Year(s)

Dimension Diagram





Unit: mm [inch]

Related Products

Mounting Accessories - Camera Mount

PMAX-0721



Junction Box (for A416, A418, ,A419, Z76)

Note: Some mounting accessories may need additional accessories for installation. Please check www.acti.com/mountingselector for more information.