

ARP670-17W

17", 1920x 1080 resolution
Rugged Portable Chassis



Features

- Rugged Aluminum Construction with shock absorbing rubber corners
- 17" LCD display 1920x 1080 resolution
Anti-reflection tempered strengthen glass
- 7-slot for ATX MB, 10-slot for SBC with Backplane
- Industrial multi-languages keyboard with touchpad
- PS2 650W power supply, 100~240VAC
- Offer 1x 5.25", 1x slim DVD-RW, 2x 3.5" drive bays
- Carrying case to manage portable PC with ease



Ordering Information

ARP670-17WUSA

17" Full HD, 7 slots for ATX MB, 2B, 1S, 1slim, VGA, Carrying case

ARP670-17WUSB

17" Full HD, 7 slots for ATX MB, 1B, 2S, 1slim, VGA, Carrying case

ARP670-17WUSAD

17" Full HD, 7 slots for ATX MB, 2B, 1S, 1slim, DVI, Carrying case

ARP670-17WUSBD

17" Full HD, 7 slots for ATX MB, 1B, 2S, 1slim, DVI, Carrying case

ARP670-S17WUSA

17" Full HD, 10 slots for SBC+PBP, 2B, 1S, 1slim, VGA, Carrying case

ARP670-S17WUSB

17" Full HD, 10 slots for SBC+PBP, 1B, 2S, 1slim, VGA, Carrying case

ARP670-S17WUSAD

17" Full HD, 10 slots for SBC+PBP, 2B, 1S, 1slim, DVI, Carrying case

ARP670-S17WUSBD

17" Full HD, 10 slots for SBC+PBP, 1B, 2S, 1slim, DVI, Carrying case

Note: Drive bay: B: 5.25", S: 3.5"

Keyboard layout: CH, FR, GR, KR, RU, SP, UK, US

Specification

Model No	ARP670-17W	ARP670-S17W
Motherboard	Support ATX M/B	Support SBC with PBP
Slots	Offer 7 expansion slots	Offer 10 expansion slots
Drive bay	1x 5.25", 1x slim DVD-RW, 2x 3.5"	
Display	17", 16: 9 TFT LCD Display, 1920x 1080 resolution Anti-reflection tempered strengthen glass	
VGA	AD conversion board, DVI interface (Option VGA)	
KB/MS	104-key industrial multi-language Keyboard/ touchpad	
Power Supply	PS2, 650W, 100~240VAC, Auto switch	
Construction	Rugged Aluminum Construction with rubber corners	
Speaker	Built-in amplified 2x 3W speakers	
Dimension	434Wx 374Hx 230D mm	
Weight	12 kgs	
Carrying Case	Padded carrying case with wheels	

Environmental Factors

	Operating	Non-Operating
Temperature	0°C~50°C	-20°C~60°C
Relative Humidity	10%~90%	10%~95%
Shock	10g, 11ms, half-Sine	30g, 11ms, half-Sine
Vibration	10-500Hz (0.4 Grms)	10-500Hz (1.12 Grms)
Approval	CE, FCC, RoHS	

