Foil Covered Industrial Keyboards - TKS (c) Rack Mounting Series



Edited with the trial version of Foxit Advanced PDF Editor

o remove this notice, visit:

www.foxitsoftware.com/shopping

















Rugged Keyboard / Drawer Combination

This aesthetically appealing mounting variant of the TKS input system is suited for the use in 19" systems. Due to the low height of 1 RU (1 rack unit = 44.45 mm) it requires very little space. The extracted drawer has an angle of 15° which allows an easy operation in standing position.

KS18347 TKS-088c-TOUCH-SCHUBL-PS/2-US	1 RU	Touchpad	IP65	482.6 x 280 x 43.7	5100 g
KS18349 TKS-088c-TOUCH-SCHUBL-USB-US	1 RU	Touchpad	IP65	482.6 x 280 x 43.7	5100 g

Other layouts, configurations and interfaces on request

1 Keyboards with pointing device: 0 °C to +70 °C

Technical Data

Switching Technology: Short Travel Keys

Switching Force: 2.6 N Switch Travel: 0.3 mm

Switching Cycles: Approx. 3 Mio. (per key)
Housing Design: 19" drawer (1 RU)

Frontpanel Material: Aluminium

Operating Temperature: -25 °C to +70 °C ¹ Storage Temperature: -25 °C to +80 °C

Technical Data of the Integrated Touchpad

Operating Principle: Capacitive
Resolution: 100-300 dpi
Dimensions: 65 x 49 mm
Active Surface: 59 x 42 mm

Foil Covered Industrial Keyboards - TKS (c) Recommounting Series



























