

# AMK508

1U, Single Slide Rail, LCD Keyboard Drawer

8 port PS2 or COMBO KVM Switch



## Features

- Meet EIA310c & IEC-3 specification
- 1U, Single Rail, built-in 17.3" LCD keyboard drawer
- 8-port PS2 or Combo KVM switch
- Built-in 17.3" LCD Monitor, 1920x 1080 resolution  
Option: 17.3", 1600x 900 resolution
- 104-key industrial keyboard with touch pad
- 1U, 520 mm short depth and lightweight
- 2 thumb screws to lock 17.3" LCD monitor
- Built-in rail self-locking device
- Tempered glass protect LCD screen

## KVM Switch

- 8 port PS2/ COMBO KVM with military industrial grade production
- Support Password protection and Server name
- Support extra daisy chain port and no waste server port for expansion
- Support Windows, DOS, Netware, Unix, Linux, iMAC, Power MAC and Sun Micro Systems with USB
- Hot Plug- add or remove connected computer without powering off the KVM switch or computer
- No software required. Easy computer selection via Front Push Button, Hot Key, OSD menu
- Auto Scan mode. Easy to monitor Server Operation
- Superior Video Bandwidth up to 200MHz
- Keyboard status restored upon Server switched
- LED display for status monitor
- Buzzer sound for Server switched confirmation

## Specification

Model No	AMK508-17	AMK508-17W
Drawer Design	1U, Single Slide Rail self-locking device for 19" rackmount	
Weight	11 kgs	
Dimension	442.4 x 44 x 520 mm (W x H x D)	
Power Supply	Built-in 60W, 90~264VAC, Operating Temp.: -20~70°C	
Construction	Heavy-duty steel	
Keyboard	104-key industrial keyboard with touchpad Option KB: CH, FR, GR, KR, RU, SP, UK, US	
Protection	Tempered glass protect LCD screen	
Physical Security	Key locking Mechanism	
Power Consumption	3 watts stand-by, 25 watts in-use	
Temperature	Operation: 0 ~ 50°C Storage: -20 ~ 60°C	
Approvals	CE, FCC class A, RoHS	

## LCD Display

Size	17.3"	17.3"
Resolution	1600 x 900	1920 x 1080

## KVM Switch

		PS2 KVM	PS2 & USB COMBO KVM
Port connection	KVM Port	8-Port	
	Max. Port	Daisy Chain up to 8 levels to support 120 sets	
Port Selection	8x Front Push Buttons, OSD Menu, Hotkey		
Switch	Port Selection	8x Front Push Buttons	
	Reset	1x push button	
	Power	1x Rocker Switch	
	LCD on/off	1x Front standby Push button	
	LCD control	4x LCD adjust push buttons	
LED	Operation	8	
	Power	8	
	Keyboard Lock	Num Lock, Caps Lock, Scroll Lock	
KVM Cable	8x 1.8m PS2 cable	8x 1.8m USB cable	

## Ordering Information

### AMK508-17PBUS

1U, 17.3", 1600x 900, 8 ports PS2 KVM switch with 8 x 1.8m PS2 cable

### AMK508-17CBUS

1U, 17.3", 1600x 900, 8 ports Combo KVM switch with 8 x 1.8m USB cable

### AMK508-17WPBUS

1U, 17.3", 1920x 1080, 8 ports PS2 KVM switch with 8 x 1.8m PS2 cable

### AMK508-17WCBUS

1U, 17.3" 1920x 1080, 8 ports Combo KVM switch with 8 x 1.8m USB cable

## Option

- 80W, 24~48 VDC Power Supply
- 1.8m, 3.0 m, 5.0 m KVM cable
- Keyboard layout: CH, FR, GR, KR, RU, SP, UK, US