# P1157E-500

15" XGA TFT Expandable Industrial Touch Panel Computer with 7th Gen Intel® Core™ i7/i5/i3, Celeron® & Pentium® Processor and 1 PCI/PCIe Slot

# **Features**


- 15" XGA TFT LCD display
- LGA1151 socket 7th gen Intel® Core™ i7/i5/i3, Celeron® & Pentium® processors
- Intel® H110 chipset
- Less screw design for easy installation
- 4 USB 3.0, 2 USB 2.0 and 4 COM ports
- One PCle x4 or one PCle slot
- Built-in speakers and optional Wi-Fi 802.11 b/g/n module
- Robust IP65 compliant aluminum front bezel
- 5 OSD keys in front panel







- 1. Display status LED x 1
- 2. SATA status LED x 1
- 3. Brightness down x 1
- 4. Brightness up x 1
- 5. Display monitor ON/OFF x 1
- 6. Volume down x 1
- 7. Volume up x 1



- 1 Line-out x 1 2. RS-232 x 1 (COM 3)
- 3. RJ-45 for Gigabit Ethernet x 1 4. RJ-45 for Gigabit Ethernet x 1
- 5. RS-232 (COM 4) x 1
- 6. PCI x 1 or PCIe x4 x 1 Card
- expansion slot
- 7. AC Plug x 1 8. Mic-in x 1
- 9. RS-232/422/485 x 1 (COM 1) 16. USB 2.0 x 2 10. RS-232 x 1 (COM 2)
- 11. USB 3.0 x 2 12. USB 3.0 x 2 13. VGA x 1
- 14. DisplayPort x 1 15. HDMI x 1
- 17. Remote Power Switch x 1
- 18. Switch for power on/off x 1

## Introduction

The P1157E-500 is a multimedia 15" touch panel PC for kiosk application. It has a fashionable mechanism design and industrial-grade material front bezel which can avoid damage from chemical corrosion. To meet the demands of multimedia application, the P1157E-500 is powered by a high performance LGA1151 socket 7th generation Intel® Core™ processor with the Intel® H110 Express chipset. It features four COM ports, two Gigabit Ethernet and up to 32GB memory of dual-channel DDR4-2133 that delivers high computing capability for high performance-demanding applications. The industrial touch panel PC is most suitable for kiosk, factory and automation.

#### Expandable for 1 PCIe or 1 PCI

The P1157E-500 has 1 PCle x4 or 1 PCl slot for expansion purpose. User can easily plug in standard half-size PCI or PCIe card based on any application needs.

### Speaker and WLAN Antenna Supported

The P1157E-500 features built-in speakers for kiosk application to display multimedia content program. It also supports WLAN module antenna (optional) for wireless network connectivity.

#### Friendly Less Screw Design

The P1157E-500 is designed with easy of maintenance in mind. There are only four screws on the back chassis, so that technicians can quickly remove the system's back cover with minimum effort.

## **Specifications**

Front Bezel	Aluminum w/ IP65/NEMA 4 rugged protection	
LCD Panel	Display Type	15" XGA TFT LCD
	Brightness	250 nits
	Resolution	1024 x 768 pixels
	Viewing Angle	160°/140°
Main System	CPU	LGA1151 socket 7th generation Intel® Core™ i7/i5/i3, Celeron® & Pentium® processor
	Chipset	Intel® H110
	System Memory	2 x 288-pin DDR4-2133 Long-DIMM, up to 32GB
	BIOS	AMI UEFI BIOS
	Storage	1 x 3.5" or 1 x 2.5" SATA HDD / 2 x 2.5" SATA HDD (optional)
	Drive	N/A
	Watchdog Timer	255 levels, 1 ~ 255 sec.

Date: 07/2017 Rev.01

## **Specifications**

IO Connector	3 x RS-232 (COM 2-4)
	1 x RS-232/422/485 (COM 1)
	1 x HDMI
	1 x VGA
	1 x DisplayPort
	4 x USB 3.0 (back)
	2 x USB 2.0 (front)
	2 x 10/100/1000 Mbps Ethernet (Intel® i219LM/i211AT)
	1 x Audio (Mic-in/Line-out)
	1 x Remote Power Switch
Expansion Interface	1 x PCle x4 or 1 x PCl
Touchscreen	5-wire resistive type
	Light transmission 79%
	1 million activations (typical) at a single point
Power Supply	100 ~ 240 VAC, 200 W
Power Consumption	97.6W
Dimensions	378.3 mm (14.89") (W) x 90 mm (3.54") (D) x 310.3 mm (12.22") (H)
Packing Dimension	510 mm (20.08") (W) x 186 mm (7.32") (D) x 532 mm (20.94") (H)
Weight(net/gross)	5.4 kg (11.90 lb)/ 7.8 kg (17.20 lb)
Environment	Operating temperature: 0°C ~ +50°C (+32°F ~ +122°F)
	Relative humidity: 10% ~ 90% @ 40°C, non-considering
	Operating vibration: 1.0G, 5 ~ 500Hz, random
Certificate	CE

## **Ordering Information**

P1157E-500 w/ PCle	15" XGA expandable industrial touch panel computer with LGA1151 socket 7th generation Intel® Core™ i7/i5/i3, Pentium® & Celeron® processor, resistive touch screen and 1 PCle x4 slot, 100 ~ 240 VAC
P1157E-500 w/ PCI	15" XGA expandable industrial touch panel computer with LGA1151 socket 7th generation Intel® Core™ i7/i5/i3, Pentium® & Celeron® processor, resistive touch screen and 1 PCI slot, 100 ~ 240 VAC

<sup>\*</sup> Specification and certifications are based on requirements and may vary.

## **Optional Accessories**

82211970070E	VESA & wall mount kit
82231870240E	Wireless LAN kit (Sparklan 251N)
E981604011	ATC10 (VESA arm clamp type)
E981604012	ATW10 (VESA arm wall mount)

## **Optional OS Installation**

Skylake: Windows® 7/8.1/10 Kabylake: Windows® 10 64-bit



# **Dimensions**

