

Quick Selection Guide

Model Name	LEAD-PD-2150 LEAD-PD-2360	LEAD-PND-2150-AV LEAD-PND-2360-AV	LEAD-PND-2150-AC LEAD-PND-2360-AC	LEAD-PND-2150-BV LEAD-PND-2360-BV	LEAD-PND-2150-BC LEAD-PND-2360-BC	LEAD-PPC-2150-A LEAD-PPC-2360-A	LEAD-PPC-2150-B LEAD-PPC-2360-B
Part Number	AL8-3081 AL8-3082	AL6-3276 AL6-3272	AL6-3275 AL6-3271	AL6-3274 AL6-3270	AL6-3273 AL6-3269	AL6-3265 AL6-3267	AL6-3266 AL6-3268
Display							
LCD Size	21.5" / 23.6"	21.5" / 23.6"				21.5" / 23.6"	
Resolution	FHD 1920 x 1080	FHD 1920 x 1080				FHD 1920 x 1080	
Brightness	250 cd/m ²	250 cd/m ²				250 cd/m ²	
Contrast Ratio	1000: 1	1000: 1				1000: 1	
Panel Type	TN	TN				TN	
Viewing Angle	170° (H) / 160° (V)	170° (H) / 160° (V)				170° (H) / 160° (V)	
Touch Screen	Projected Capacitive Multi-Touch	Projected Capacitive Multi-Touch				Projected Capacitive Multi-Touch	
System							
SOC	N/A, Monitor Only	AllWinner A83T Octa-Core Cortex™ A7 CPU				Intel® Atom® Dual-Core x5-E3930 (1.3GHz, up to 1.8GHz)	
Memory		1GB DDR3L on board				8G DDR3L/1600 SO-DIMM	
LAN Chip		Realtek® RTL8211E				Intel® WGI210IT	
Audio Codec		AllWinner AXP813				Realtek® ALC892	
Storage Device		16G eMMC on board				128G TLC mSATA	
OS		Android 6.0				Windows 10 IoT / Android 6.0 / Linux™ Ubuntu 16.10	
I/O Interface							
Serial Port	N/A	N/A	1 x Tx/Rx for OSD function	N/A	1 x Tx/Rx for OSD function	1 x RS-232/422/485	
Display	Input: 2 x HDMI, 1 x VGA	Input: 1 x HDMI, 1 x DP, 1 x VGA	Input: 1 x HDMI, 1 x DP	Input: 1 x HDMI, 1 x DP, 1 x VGA	Input: 1 x HDMI, 1 x DP	Output: 1 x HDMI	
USB	Upstream: 1 x USB 2.0 Type B Downstream: 1 x USB 2.0 Type A	2 x USB 2.0 1 x Micro USB for Touch only				2 x USB 3.0	
Ethernet	N/A	1 x Gigabit Ethernet				2 x Gigabit Ethernet	
Audio	2 x 2W Speaker, 1 x Line out, 1 x Line in	2 x 3W Speaker				2 x 3W Speaker	
OSD Key	Power / Menu / Right / Left / Auto	Power / Menu / Right / Left / Auto				N/A	
Power							
Power Input	DC 20V via DC Jack	DC 12V via DC Jack		DC 24V via 3-pin terminal block connector		DC 12V via DC Jack	DC 24V via 3-pin terminal block connector
Power Supply	45W AC-DC Adapter, Power Cord	40W AC-DC Adapter		60W AC-DC Adapter		65W AC-DC Adapter	60W AC-DC Adapter
Environmental							
Mounting (mm)	Standalone; VESA® Mount 75 x 75	Standalone; VESA® Mount 75 x 75				Standalone; VESA® Mount 75 x 75	
Accessory	1 x HDMI cable, 1 x USB 2.0 Type B to A cable	1 x VGA cable	N/A	1 x VGA cable	N/A	N/A	
OP /Storage Temperature	0~40°C / -25~55°C	0~50°C / -20~60°C				0~50°C / -20~60°C	
IP Protection	IP65 (Front)	IP65 (Front)				IP65 (Front)	
Certificate	CE / FCC Class B	CE / FCC Class A				CE / FCC Class B	