

DAQ/DAQe-2213/2214

16-CH 16-Bit 250 kS/s Low-Cost Multi-Function DAQ Cards



Ordering Information / Quick Selection Guide

| Model Name | Analog Input | | | | Analog Output | | | DIO | Timer/Counter |
|---------------|-----------------|------------|---------------|------------------|-----------------|------------|---------------|-----------------|-----------------|
| | No. of channels | Resolution | Sampling rate | Input range | No. of channels | Resolution | Sampling rate | No. of channels | No. of channels |
| DAQ/DAQe-2213 | 8 DI/16 SE | 16 Bit | 250 kS/s | ±1.25 V to ±10 V | - | - | - | 24-CH 8255 PIO | 2-CH, 16-Bit |
| DAQ/DAQe-2214 | 8 DI/16 SE | 16 Bit | 250 kS/s | ±1.25 V to ±10 V | 2 | 12 Bit | 1 MS/s | 24-CH 8255 PIO | 2-CH, 16-Bit |

Specifications

| Model Name | DAQ/DAQe-2213 | DAQ/DAQe-2214 |
|--------------------------------------|---|---|
| Analog Input | | |
| Resolution | 16 Bit, no missing codes | |
| Number of channels | 16 single-ended or 8 differential (software selectable per channel) | |
| Channel gain queue size | 512 | |
| Maximum update rate | 250 kS/s | |
| Programmable gain | 1, 2, 4, 8 | |
| Bipolar input ranges | ±10 V, ±5 V, ±2.5 V, ±1.25 V | |
| Unipolar input ranges | 0-10 V, 0-5 V, 0-2.5 V, 0-1.25 V | |
| Offset error | ±1 mV | |
| Gain error | ±0.06% of FSR | |
| Input coupling | DC | |
| Overvoltage protection | Power on: Continuous ±30 V, Power off: Continuous ±15 V | |
| Input impedance | 1 GΩ/100 pF | |
| Trigger sources | Software, external digital/analog trigger, SSI bus | |
| Trigger modes | Pre-trigger, post-trigger, middle-trigger, delay-trigger, and repeated trigger | |
| FIFO buffer size | 1 k samples | |
| Data transfers | Polling, scatter-gather DMA | |
| Analog Output | | |
| Number of channels | - | 2 voltage outputs |
| Resolution | - | 12 Bit |
| Output ranges | - | 0-10 V, ±10 V, 0-AOEXTREF, ±AOEXTREF |
| Maximum update rate | - | 1 μs |
| Slew rate | - | 20 V / μs |
| Settling time | - | 3 μs to ±0.5 LSB accuracy |
| Offset error | - | ±2 mV |
| Gain error | - | ±0.04% of max. output |
| Driving capacity | - | ±5 mA |
| Stability | - | Any passive load, up to 1500 pF |
| Trigger sources | - | Software, external digital/analog trigger, SSI bus |
| Trigger modes | - | Post-trigger, delay-trigger, and repeated trigger |
| FIFO buffer size | - | 1 k samples |
| Data transfers | - | Programmed I/O, scatter-gather DMA |
| Digital I/O | | |
| Number of channels | 24-CH 8255 programmable input/output | |
| Compatibility | 5 V/TTL | |
| Data transfers | Programmed I/O | |
| General-Purpose Timer/Counter | | |
| Number of channels | 2 | |
| Resolution | 16 Bit | |
| Compatibility | 5 V/TTL | |
| Base clock available | 40 MHz, external clock up to 10 MHz | |
| General Specifications | | |
| Auto Calibration | Yes (+5 V, ±2 ppm/°C) | |
| Dimensions | 175 mm x 107 mm (6.82" x 4.17") (not including connectors) (DAQ-2213/2214) 168 mm x 107 mm (6.55" x 4.17") (not including connectors) (DAQe-2213/2214) | |
| Connector | 68-pin VHDCI female x 2 | |
| Operating temperature | 0°C to 55°C (32°F to 131°F) | |
| Storage temperature | -20°C to 70°C (-4°F to 158°F) | |
| Humidity | 5 to 95%, non-condensing | |
| Power requirements | +5 V 1.2 A typical (DAQ-2213) +3.3 V 0.84 A, +12 V 0.604 A typical (DAQe-2213) | +5 V 1.2 A typical (DAQ-2214) +3.3 V 0.77 A, +12 V 0.572 A typical (DAQe-2214) |

Features

- Supports a 32-Bit 3.3 V or 5 V PCI bus (DAQ-2213, DAQe-2214)
- x1 lane PCI Express® Interface (DAQe-2213, DAQe-2214)
- Onboard 1 k-sample A/D FIFO
- Bipolar or unipolar analog input ranges
- Programmable gains: x1, x2, x4, x8
- 512-configuration channel gain queue
- Scatter-gather DMA
- 2-CH 12-Bit multiplying analog outputs with waveform generation (DAQ/DAQe-2214)
- Onboard 1 k-sample D/A FIFO (DAQ-2214, DAQe-2214)
- 24-CH TTL digital input/output
- 2-CH 16-Bit general-purpose timer/counter
- Analog and digital triggering
- Fully auto calibration
- Multiple cards synchronization through SSI (System Synchronization Interface) bus
- Supported Operating System
 - Windows 7/8 x64/x86, Linux
- Driver and SDK
 - LabVIEW, MATLAB, C/C++, Visual Basic, Visual Studio.NET
- Software Utility
 - AD-Logger

Terminal Boards & Cables

- DIN-68S-01
- ACL-10568-1
- ACL-SSI-2/3/4 (for DAQ/DAQe-2214)

* For more information on mating terminal board and cables, please refer to P3-48/49.