

Specifications

I/O Connector	2 x RS-232/422/485 (COM 1/2) 1 x Switch for power on/off (ATX) 1 x Audio (Line-out) 2 x USB 3.0, 2 x USB 2.0 2 x 10/100/1000Mbps Ethernet
Expansion Interface	2 x PCIe Mini Card slots
Touchscreen	Projected Capacitive multi-touch
Power Supply	1. DC version : 9~36VDC 2. AC version : 12VDC w/adapter
Dimensions	396 mm (15.6") (W) x 53.9 mm (2.12") (D) x 247.1 mm (9.73") (H)
Packing Dimensions	525 mm (20.67") x 470 mm (18.51") x 186 mm (7.32")
Weight (net/gross)	5.0 kg (11.02 lb)/7.0 kg (15.43 lb)
Environment	Operating temperature: -10°C ~ +50°C (+14°F ~ +122°F) Storage Temperature: -20°C ~ +60°C (-4°F ~ +140°F) Relative humidity: 20% ~ 90% @ 40°C; non-condensing Operation vibration: 2 G, 10 ~ 500Hz, random for CompactFlash™
Certificate	CE

* W.T.: Wide Temperature. All W.T. supported products have to be sorted by Axiomtek.

Ordering Information

GOT3157W-834-PCT-DC	15.6" WXGA TFT fanless multi touch panel computer with Intel® Celeron® J1900 and PCT touch, DC version (-10°C ~ +50°C)
GOT3157W-834-PCT-J	15.6" WXGA TFT fanless multi touch panel computer with Intel® Celeron® J1900 and PCT touch, AC version (-10°C ~ +50°C)

Optional EOS Installation

WES7
WE8S

Optional OS Installation

Windows® 8
Windows® 7



▲ Ideal for factory automation & self-service kiosk in retail

Dimensions

